

Technical Data Sheet

Capatue™ SCA-V71C

Abstract

SCA-V71C is a vinyl functional silane making them suitable to be used as a crosslinker in making crosslinking organic polymers. Adhesion promoter of vinyl, acrylic resins.

Could be soluble in water with adequate stirring at concentrations up to 5 per cent.

Chemical Name

Vinyl tris(2-methoxyethoxy) silane

Synonyms

6-Ethenyl-6-(2-methoxyethoxy)-2,5,7,10-tetraoxa-6-silaundecane;
Tris(2-methoxyethoxy)vinylsilane

CAS Registry Number

1067-53-4


EINECS

213-934-0

Molecular Formula

$C_{11}H_{24}O_6Si$

Molecular Structure



Molecular Weight

280.39

Equivalents

Product	Supplier
Silquest® A-172	Momentive (formerly OSi Specialties)
Z-6172	Dow Corning
VTMOEO	Evonik (formerly Degussa)
GENIOSIL® GF 58	Wacker

[Http://www.capatue.com](http://www.capatue.com) E-mail: info@capatue.com

Tel: +86-25-8637 1192, 8637 1193 Fax: +86-25-8637 1191 ext. 0

Add: Block E4, Zidong Industry Park, 2 Zidong Road, Maqun Town, Qixia Dist., Nanjing, Jiangsu, China, 210023



KBC-1003

Shin-Etsu

Typical Properties

Index	Value
Appearance	Colorless, transparent liquid
Specific Gravity (ρ_{20}), g/cm ³	1.0330
Boiling Point (760mmHg), °C	285
Refractive Index (n_D^{25})	1.4270
Flash Point, °C	92
Solubility	Soluble in alcohol, ketone, aether, benzene and most aliphatic esters, soluble in water as well with adequate stirring at concentrations up to 5%.

Applications and Performance

1. Inorganic mineral fillers surface treatment: Improves the compatibility of surface treated with organic resins, enhances the mechanic strength and electrical properties of the mineral-filled composites. Particularly suitable in water system modification method, could be add in water solution directly.
2. Emulsion polymerization: As a monomeric vinyl functional silane in vinyl, vinyl acrylic and acrylic resin, this vinyl silane can be added as monomers during emulsion during polymerization to form silane modified latexes. The silane in such latexes functions as crosslinkers, forming very stable Si-O-Si chain.
3. Adhesives, sealants and hot melt: Excellent adhesion to a wide range of inorganic substrates such as metal, glass and concrete, the suitable resins include acrylic, vinyl and vinyl acrylic.

Packing

The regular packing of this product is 25kg plastic pail, 200L steel drums and 1000L immediate bulk container.

[Http://www.capatue.com](http://www.capatue.com) E-mail: info@capatue.com

Tel: +86-25-8637 1192, 8637 1193 Fax: +86-25-8637 1191 ext. 0

Add: Block E4, Zidong Industry Park, 2 Zidong Road, Maqun Town, Qixia Dist., Nanjing, Jiangsu, China, 210023



Storage and Shelf Life

Should be stored in dry, cool, ventilated room; keep away from water, moisture, high temperature and fire. This product has a shelf life of at least 12 months if stored in tightly closed original container at room temperature.

If this product is kept beyond the shelf life recommend on the product label, it is not necessarily unusable, but a quality control should be performed on the properties relevant to the application.

Product Safety and Handling

When considering the use of any Capatue products in a particular application, you should read our latest Material Safety Data Sheets (MSDS) thoroughly for handling instructions, personal protective equipment if necessary, other safety issue and toxicological data as well as for information on proper transportation, storage and use to ensure that the use you intend can be accomplished safely. Our latest Material Safety Data Sheets (MSDS) and other product safety information are available at www.capatue.com or upon request, from our customer service department.

Use of other material in conjunction with Capatue products may require addition precautions. Please review and follow the safety information provided by the manufacturer of such other materials.

This product is for industry use only; it is neither tested nor represented as suitable for food, medical or pharmaceutical uses.

Limited Warranty Information

The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that Capatue's products are safe, effective, and fully satisfactory for the intended end use.

Suggestions of use shall not be taken as inducements to infringe any patent.

Capatue's sole warranty is that the product will meet the Capatue sales specifications in effect at the time of shipment.

Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.

Capatue specifically disclaims any other express or implied warranty of fitness for a particular purpose or merchantability.

Capatue disclaims liability for any incidental or consequential damages.

Customer must do enough tests before their regular production to ensure that our product is suitable for their specific application.